```
Andrei Faraon@Ciofciofel ~
$ startxwin.sh

Andrei Faraon@Ciofciofel ~
$ Welcome to the XWin X Server
Vendor: The Cygwin/X Project
Release: 6.8.2.0-2

Contact: cygwin-xfree@cygwin.com

XWin was started with the following command line:

XWin -multiwindow -clipboard -silent-dup-error

_XSERVTransmkdir: Cannot create /tmp/.X11-unix with root ownership
winValidateArgs - g_iNumScreens: 1 iMaxConsecutiveScreen: 1
(II) XF86Config is not supported
(II) See http://x.cygwin.com/docs/faq/cygwin-x-faq.html for more information
(==) FontPath set to "/usr/X11R6/lib/X11/fonts/misc/,/usr/X11R6/lib/X11/fonts/TT
F/,/usr/X11R6/lib/X11/fonts/Type1/,/usr/X11R6/lib/X11/fonts/CID/,/usr/X11R6/lib/
X11/fonts/75dpi/,/usr/X11R6/lib/X11/fonts/100dpi/"
winDetectSupportedEngines - Windows NT/2000/XP
winDetectSupportedEngines - DirectDraw installed
winDetectSupportedEngines - DirectDraw4 installed
winDetectSupportedEngines - Returning, supported engines 00000007
winSetEngine - Multi Window or Rootless => ShadowGDI
winAdjustVideoModeShadowGDI - Using Windows display depth of 32 bits per pixel
winAllocateFBShadowGDI - Creating DIB with width: 1400 height: 1050 depth: 32
winFinishScreenInitFB - Masks: 00ff0000 0000ff00 000000ff
winInitVisualsShadowGDI - Masks 00ff0000 0000ff00 000000ff BPRGB 8 d 24 bpp 32
null screen fn ReparentWindow
null screen fn RestackWindow
InitQueue - Calling pthread_mutex_init
InitQueue - pthread_mutex_init returned
InitQueue - Calling pthread_cond_init
InitQueue - pthread_cond_init returned
winInitMultiWindowWM - Hello
winInitMultiWindowWM - Calling pthread_mutex_lock ()
winMultiWindowXMsgProc - Hello
winMultiWindowXMsgProc - Calling pthread_mutex_lock ()
MIT-SHM extension disabled due to lack of kernel support
XFree86-Bigfont extension local-client optimization disabled due to lack of shar
ed memory support in the kernel
(--) Setting autorepeat to delay=500, rate=31
(--) winConfigKeyboard - Layout: "00000409" (00000409)
(--) Using preset keyboard for "English (USA)" (409), type "4"
Rules = "xorg" Model = "pc105" Layout = "us" Variant = "(null)" Options = "(null
)"
(--) 3 mouse buttons found
Could not init font path element /usr/X11R6/lib/X11/fonts/TTF/, removing from li
st!
Could not init font path element /usr/X11R6/lib/X11/fonts/Type1/, removing from
list!
Could not init font path element /usr/X11R6/lib/X11/fonts/CID/, removing from li
st!
Could not init font path element /usr/X11R6/lib/X11/fonts/100dpi/, removing from
 list!
winPointerWarpCursor - Discarding first warp: 700 525
winInitMultiWindowWM - pthread_mutex_lock () returned.
winProcEstablishConnection - Hello
winInitClipboard ()
winProcEstablishConnection - winInitClipboard returned.
winClipboardProc - Hello
DetectUnicodeSupport - Windows NT/2000/XP
winClipboardProc - DISPLAY=127.0.0.1:0.0
winMultiWindowXMsgProc - pthread_mutex_lock () returned.
winMultiWindowXMsgProc - pthread_mutex_unlock () returned.
winMultiWindowXMsgProc - DISPLAY=127.0.0.1:0.0
winInitMultiWindowWM - pthread_mutex_unlock () returned.
winInitMultiWindowWM - DISPLAY=127.0.0.1:0.0
winClipboardProc - XOpenDisplay () returned and successfully opened the display.

winInitMultiWindowWM - XOpenDisplay () returned and successfully opened the disp
lay.
winMultiWindowXMsgProc - XOpenDisplay () returned and successfully opened the di
splay.
$
```

```
Andrei Faraon@Ciofciofel ~
$
```


school Read how I did it - You can too!
www.myGMATscore.com

Stanford Park
Compare Prices and Find Great Hotel Deals for Your Trip at TripAdvisor!
www.TripAdvisor.com

Related Pages

SQuirreL SQL Client 1.1
OSDir - May 18, 2005
The SQuirreL SQL Client is an open-source Java application for ...

About these links

Check spelling

start | Gmail - question - Mic... | Palm Desktop | 11:51 AM